

Paintspray Hose:

A high pressure hose with a Hytrel tube, excellent resistance to most paints and solvents. It has one or two layers of steel braiding to give an extremely flexible yet durable hose for use in arduous conditions. Lengths are available to suit your requirements and applications.

All assemblies are fully pressure tested prior to dispatch.

Maximum working pressure: 1/4" bore - 290 Bar 3/8" bore - 222 Bar
1/2" bore - 190 Bar

Sewer Jetting Hose:

Lightweight, easy to handle, high pressure jetting hose. Thermoplastic construction with a unique textile reinforcement gives outstanding resistance to abrasion for arduous working conditions.

Bore size range - 25 mm to 38 mm.
Coil length - 120 mtr.

Flexible Metallic Hose:

Square lock and fully packed interlock construction. Widely used in the conveyance of granular materials, suitable for exhaust systems on petrol or diesel engines. Available in Electro galvanised steel or stainless steel.

Bore size range - 19 mm to 200 mm.
Lengths to suit application.

General Purpose Ducting:

We offer a most extensive range of ducting for handling air, fumes, dust and bulk materials. Materials available are PVC, aluminised cloth, rubber coated synthetic cloth to handle temperatures of up to 320°C, to meet the requirements of most industrial, pharmaceutical, mining, civil engineering and food handling applications. Our experienced sales team will advise you of the most suitable product for your particular application.

Polyurethane Ducting:

A heavyweight yet very flexible polyurethane ducting with a relatively smooth bore ideal for the suction and transportation of highly abrasive materials, oily substances, pharmaceutical powders and granules.

Working temperature range:
-40°C to +100°C.
Bore size range - 20 mm to 408 mm.
Coil length - 10/15 mtr.

Mining Ducting, Semi-rigid:

Used for underground ventilation, fully anti-static & flame retardant PVC coated nylon with spring steel wire helix, extremely tough for arduous working conditions. A choice of pitch helix, styles, end terminations and accessories are available.

Bore size range - 100 mm to 900 mm.
Maximum length - 8 mtr.

Mining Ducting, Layflat:

Used for underground ventilation, flame retardant and anti-static. Available with hooks and hanging wire or to fit into cassette systems.

Bore size range - 100 mm to 900 mm.
Maximum length - 200 mtr.

