




Shotblast Hose:

High abrasion resistant and flexible hose, fully anti-static, ideal for sand, shot and grit blasting, also suitable for water slurry, dry powder & plaster delivery applications up to 40 Bar working pressure.


Size range - 6 mm to 152 mm.

Coil length - 20 mtr, 40 mtr & 61 mtr.



Composite Hose:

A comprehensive range of flexible fully anti-static thermoplastic composite hoses providing the vital link in the bulk transfer of hydro carbons & chemical liquids or powders.



Steam Hose:

a. High strength textile yarn reinforcement for saturated steam at 100 Psi with a working temperature of 170°C maximum.

Fully complies to BS 5122 class A type 2 specification.

b. Steel wire braid reinforcement for use with superheated steam at 250 Psi with working temperature of 235°C. Fully complies with requirements of BS 5342 class A type 2.

Size range - 13 mm to 102 mm.

Coil length - 20 mtr & 40 mtr.



Bulk Material Handling:

A flexible, rugged hose, fully anti-static with soft cuffed or enlarged ends. Smooth bore abrasion resistant lining to convey materials such as dry cement powder, sand, fly ash and most industrial abrasive media. Custom built to suit your requirements.

Size range - 52 mm to 610 mm.

Length available - 1 mts to 15 mtr.

Size range - 12.5 mm to 152 mm.

Coil length - 20 mtr & 40 mtr.